



ARTICULADAS ELÉCTRICAS

	HA12CJ	HA12CJ +	HA12IP	HA15IP	HA20LE *	HA20LEPRO *
Altura de trabajo	11.68 m	11.68 m	12 m	14.87 m	20.67 m	20.76 m
Altura plataforma	9.68 m	9.68 m	10 m	12.87 m	18.67 m	18.76 m
Alcance máximo	6.94 m	7.22 m	6.5 m	8.65 m	11.91 m	11.91 m
Punto de articulación	4.74 m	4.74 m	5.3 m	6.25 m	8.43 m	8.52 m
Capacidad máxima	250 Kg	230 Kg	230 Kg	230 Kg	250 Kg	250 Kg
Dimensiones cesta	1.14 x 0.8 m	1.14 x 0.8 m	1.20 x 0.8 m	1.15 x 0.8 m	1.83 x 0.8 m	1.83 x 0.8 m
Largo replegada	5.36 m	5.64 m	5.40 m	6.65 m	8.45 m	8.54 m
Ancho	1.2 m	1.2 m	1.35 m	1.52 m	2.41 m	2.41 m
Altura replegada	1.99 m	1.99 m	2.06 m	2.1 m	2.4 m	2.5 m
Pendiente máxima	25%	25%	25%	25%	45%	45%
Energía	48 V - 320 Ah	48 V - 320 Ah	48 V - 345 Ah	48 V - 345 Ah	12x6 V-435 Ah	12x6 V-435 Ah
Peso total	7,065 Kg	7,110 Kg	5,945 Kg	7,230 Kg	9,375 Kg	9,785 Kg

*Los modelos seleccionados cuentan con:

ACTIV' SHIELD BAR 2.0: Previene los riesgos de atrapamiento
 ACTIV' SCREEN: Herramienta de diagnóstico incorporada

